

Please amend the present application as follows:

**Claims**

The following is a copy of Applicant's claims that identifies language being added with underlining ("\_\_\_\_") and language being deleted with strikethrough ("———") or brackets ("[[ ]]"), as is applicable:

1. (Previously presented) A method for implementing device regionalization, comprising:

identifying with a printer a region code stored on a component installed within the printer, the region code identifying a particular geographical region; and

locking a geographical region for the printer to be the geographical region identified by the region code such that only components intended for sale in that geographical region can be used with the printer.

2. (Canceled)

3. (Previously presented) The method of claim 1, wherein identifying a region code comprises reading a region code embedded within memory of a print cartridge that is installed within the printer.

4. (Previously presented) The method of claim 1, wherein locking a geographical region comprises storing the identified region code in memory of the printer.

5. (Canceled)

6. (Previously presented) The method of claim 1, wherein locking the region code comprises determining the number of pages that have been printed by the printer and locking the region code if the number of pages reaches a predetermined threshold.

7. (Previously presented) The method of claim 1, further comprising providing the region code to a user computer.

8. (Previously presented) The method of claim 7, further comprising accessing a database on the user computer that cross-references the region code with components available for use with the printer to identify components that can be presented to a user for purchase.

9. (Previously presented) The method of claim 7, wherein providing the region code comprises providing the region code to a device driver that executes on the user computer and wherein accessing a database comprises accessing the database with the device driver.

10. (Previously presented) A computer-readable memory that stores a system for implementing device regionalization that executes on a printer, the system comprising:

means provided on the printer for reading a region code embedded within a device component installed within the printer, the region code identifying a particular geographical region; and

means provided on the printer for locking a geographical region for the printer to be the geographical region identified by the region code such that only components intended for sale in that geographical region can be used with the printer.

11. (Canceled)

12. (Previously presented) The computer-readable memory of claim 10, further comprising means for providing the region code to a device driver that executes on a user computer.

13-14. (Canceled)

15. (Previously presented) The computer-readable memory of claim 10, wherein the means for locking a geographical region comprise means for determining the number of pages that have been printed and comparing that number with a predetermined threshold.

16. (Previously presented) A computer-readable storage medium that stores:  
logic for reading a region code from a device component installed in a printer, the  
region code identifying a particular geographical region;  
logic configured to store the read region code within printer memory; and  
logic configured to provide the stored region code to a device driver that  
executes on a user computer.

17. (Previously presented) The computer-readable storage medium of claim  
16, wherein the logic configured to store is further configured to lock the region code on  
the printer, such that only components intended for sale in the identified geographical  
region can be used with the printer.

18. (Previously presented) The computer-readable storage medium of claim  
16, wherein the logic configured to store is configured to lock the region code after a  
predetermined number of pages have been printed by the printer.

19. (Previously presented) The computer-readable storage medium of claim  
16, wherein logic configured to provide the region code is configured to provide the  
region code to the device driver when the device driver communicates with the printer to  
send the printer a print job.

20-23. (Canceled)

24. (Previously presented) A printer, comprising:

a processing device; and

memory including a region identification system that is configured to read a region code from an encoded component installed within the printer, the region code identifying a particular geographical region, and to lock a geographical region for the printer to be the geographical region identified by the region code such that only components intended for sale in that geographical region can be used with the printer.

25. (Previously presented) The device of claim 24, wherein the region identification system is configured to lock the region code for the printer only after a predetermined criterion is satisfied.

26. (Previously presented) The device of claim 25, wherein the region identification system is configured to lock the region code after a predetermined number of pages have been printed by the printer.

27. (Previously presented) A computer-readable storage medium that stores a driver comprising:

a component identification module that is configured to receive a region code from a printer that is controlled by the device driver, the region code identifying a particular geographical region, to access a database using the region code a device model to determine the components that pertain to the geographical region and the printer and therefore are available for use with the printer, and to identify the determined components to a device user.

28. (Previously presented) The computer-readable storage medium of claim 27, wherein the component identification module is configured to identify a part or order number to the device user to enable the user to purchase a replacement component.